Saeco

www.gastromatic.at



A-7000 Eisenstadt, Industriestraße 23-27 Tel.: 02682 / 66 111, Fax: 66 111 85



Articol

Description

Here is the new Saeco Artico line. This successful line of snack & food machines has a completely new design and modern graphics. Artico L is the new generation of 8-spirals snack & food vending machines with 6 and 7 removable trays for dispensing snacks, cold beverages in cans or bottles and, in the food configuration (from 0° to 4°C), also sandwiches and fresh products.

It matches perfectly with the freestanding hot vending machines Cristallo Evo 600, with which can share the payment system, and Atlante Evo 500/700.

Accessories

- RSI programming key
- Eva-Dts kit
- Wall mounting brackets kit

Main features

- Programmable temperature (snack or food)
- Optimized ventilation to reduce energy consumption
- Possibility to create menus for selling more combined products
- New 16-bit electronics
- Possibility to install 3 payment systems at the same time
- Accepts the most commonly used parallel and standard MDB, BDV and Executive payment systems

User interface

- Backlit capacitive keyboard with 12 buttons
- 128×64 pix graphic display
- Antivandalic coin introduction as standard

Technical data Structural specifications

Dimensions ($w \times h \times d$)	890 × 1830 × 793 mm
Overall size with open door	1495 mm
Weight	270 kg
Electrical specifications	
Power supply	230 V/50 Hz
Power consumption	500 W
Consumption	2514 kw/h
Other specifications	
Number of trays	6 - 7
Bottle tray	48 bottles
Can tray	48 cans
Snack tray	according to the spiral type
Number of spirals	48 - 56
Available spirals	24 (19 products) to 80 (6 products)
Adjustable temperature	
Food configuration snack food/Tetra Pak	8°C - 16°C 0°C − 4°C

Technical specifications


- Programmable temperature based on product assortment
- The removable slot allows servicing the machine without interacting with the refrigerated area. The slot supports CPU, payment systems, display, keypad and closes the cash box area.
- Steel-sheet structure
- Photocells
- Wide product dispensing compartment, with opening to the outside
- Height of the cells containing the trays equal to 1240 mm
- Removable plastic trays, which provide a suitable resistance to weight. The tray position can be easily adjusted with 15 mm shifts.
- Self configuration with automatic reset at every machine start
- LED lighting
- Programming of sale prices
- Programmable RS1 Rielda lock


Artico L

• CE, IMQ approved



Configurations







+
Cristallo Evo 600



+
Atlante Evo 500



+
Atlante Evo 700